C-HM1

- Standard Capacity: 100 LT/H (30 GAL/H)
- Standard Pressure: 400 BAR (5.800 PSI)
- Standard Power: 2.2 kW



Advantages

- High capacity at low RPM, saving energy
- Efficient homogenization
- Low maintenance costs
- Easy access for maintenance
- Hygienic and ergonomic desing
- Immediate spate parts availability
- Competitive pricing and on time delivers Pro-active competent customer service
- and support Suitable for abrasive and high viscocity
- products

Options

- 2nd stage homogenizing head
- Plungers in ceramic
- Automation and remote control
- Digital pressure gauge
- Variable frequency drive (VFD)
- Inlet pressure gauge
- Aseptic and sanitary version
- ATEX Compliance
- cGMP support and certification

APPLICATION



Dairy

Milk. UHT Milk. Soy Milk, Oat Milk Yoghurt, Ayran Kefir Ice Cream Gelato

Labneh, Kashta Cream Cheese Mascarpone Desserts Milk Powder Spray Dryed Products



Food & Beverage

Fruit Juices Fruit Concentrate Aromas / Cloudifiers Food Emulsions Ketchup / Tomato Paste Margarine

Tahina Hummus Caramel Sauce Topping Sauce Dressing Peanut / Hazelnut Paste



Chemicals and Petrochemical

Greas Lubricants Paraffin Emulsions Silicone Emulsions Wax Emulsions Mineral oil Emulsions **Polymer Suspensions** Fungicides, Herbicides Latex Paint Detergents



Cosmetics

Hair Products **Beauty Creams** Moisturizing Creams Lotion Shampoos Half Conditioners

Nail Polishes Lipsticks Toothpaste Collagen Perfume Waxes



Pharmaceuticals

Antibiotics Creams Antacids **Tablet Coatings** Liposomes **Ointments**


Syrups Vitamins **Proteins** Gels Vaccines



Biotechnology

Proteins Yeast Vitamins Bacteria Enzymes Liposomes Viruses Moss **Probiotics** Microorganisms Algae Celluloses

C-HM1



Compression Head

- · Moonoblock head formed by single forged block in high quality SS alloy
- · 3-D CAD design, engineered using, FEM and CFD Analysis
- INNNOTION function integrating technical R&D and technology focus.
- Surface Roughness:Ra<1.6μm,Ra<0.8μm,Ra<0.5μm (electropolished)
- Designed to avoid sharp edges and stress concentration
- Overpressure relief valve installed
- 10-year warranty against cracks and defects

Homogenizing Valve

- · Designed to be energy efficient with high stability
- · Homogenization pressure pneumatric regulating system
- Tungsten carbide, cobalt cardibe, Zirconium ceramic and silicon nitride, solid ceramic available as option

Pump Valves

- · Mushroom and ball type in high wear resistant SS alloy
- Stellite and tungsten carbide materials available as option
- · Designed symmetrically to be used twice-once on each time

Pump Body (Gearbox)

- · High resistant resin reinforced cast iron
- · Heavy duty engineered and vibrationless
- AC motor drive through V belts and pulleys with integrated gearbox

Frame

· Thick stainless-steel material is used for heavy load

Plungers

- · Chrome coated stainless-steel alloy
- · Ceramic, HCR chromium and tungsten carbide coated as option
- · Solid ceramic as option

Sealing Components

- Long Lasting Food-grade hygienic material
- EPDM, NBR, FKM, PE, PTFE, ZEDEX, PEEK, TIVAR, Kevlar Available with FDA approval

Technical Data

Motor Power	2.2 kW
Number of Plungers	3
Lubrication Oil ISO VG 150	2.5 L
Gear Reducer Oil ISO VG 320	0.4 L
Water Consumption	40 L

Performance

Max.Capacity		Max. Pressure	
LT/H	GAL/H	BAR	PSI
300	80	170	2500
250	70	200	2900
200	50	250	3600
150	40	300	4350
100	30	400	5800
80	20	600	7250
60	15	800	8700
50	13	1000	14500
40	10	1200	17400
25	5	1500	22000

*Special desing & manufacturing are made for different pressures & capacities.





● +90 232 257 54 44
■ info@hommak.com ● www.hommak.com
■ Balkan Caddesi No:29 Yazıbası / Torbalı - IZMIR







